

TD11520 Longitudinal Channelizer Systems



The TD11520 utilizes the proven Boomerang Flexible Delineator with the Park-N-Guard Speed Bump to allow for a multitude of Channelizing designs. The unique modular style allows for great varieties in the spacing of the Delineator Posts in mountable median separation systems. The TD11520 is Perfect for emergency vehicle crossovers, railroad crossings, bicycle lanes, bus lanes, school zone drop-offs, and many other situations.



430 North Varney Street Burbank, CA 91502 Tel: 877 843 9757 Fax: 818 841 5096
Email: sales@traffiewks.com Web: www.traffiewks.com



Shown at left: 44" between post centers.
Each Speed Bump is 18" long, so adding additional bumps will increase distance between post centers by that amount.



Install the TD11520 by applying epoxy to the Delineators and Speed Bumps and then affix to the clean road surface. Additionally, Speed Bumps may be installed using standard 3/8 inch anchor bolts. Complete installation instructions will accompany each order.

Boomerang Flexible Delineators are available in 36" high (standard). Other sizes are available upon request.
Tube Colors: Yellow, White, Orange.
Tube diameter is 2.250.
Please specify sheeting desired when ordering.
All sheeting is ASTM 4956 compliant.
Tube Material: 100% Post- Consumer Recycled HDPE Plastic with UV-stabilizers added.



Speed Bumps are 18" long, 8" wide and 1.500" high.
Bolt holes (2 places) are for 3/8 anchor bolts, 14.250 apart.
Material: Recycled Plastic with UV stabilizers and cold weather impact modifiers.
Standard colors: Yellow or White. Other colors available.

